

TECHNICAL DATE SHEET

page 1/2

UVC multiple-lamp systems 400 W - COMPACT T

SYSTEM TYPE			3 AF400 T
Product			AQUAFIDES
Manufacturer			AQUAFIDES
OPERATING RANGE			3 AF400 T
Flow rate calculated	from - up to	m ³ /h	3,2 - 264,1
Head loss flow-max certified (without geodetical height)			0,275
Fluenz - calculated PSS (Point-Source-Summation)			400
Tr100 @ 254nm	from - up to	%	1 - 100
Tr50 @ 254nm	from - up to	%	10 - 100
Tr10 @ 254nm	from - up to	%	63,1 - 100
SSK @ 254nm	from - up to	m-1	20 - 0
Temperature of process water*	from - up to	°C	0 - 65
CONTROL - CABINET			3 AF400 T
Type			DigiSys with Slave Card 3 AF 300-400
System design			Bus-RS485
Control mode			digital
Control data and software update access			USB
Software service and settings via laptop			yes
Control display multi 3-colours (green, yellow and red)		lines	4
Control button for the operation of the system		button	5
Product (control-cabinet)			Rittal AE
Material (control-cabinet)			steel plate coated
Colour (control-cabinet)		grey RAL	7035
Dimensions	width	mm	760
	height	mm	760
	depth	mm	300
Weight			kg 56
Operating voltage (nominal voltage)		V / Hz	230 / 50
Operating connection		0	1L / N / PE
Total consumed power (normal operation)		W	1.250
Power factor (normal operation)		cos φ	0,99
Current load per phase (by nominal voltage) max.		A	5,5
Protection class		IP	55
Feed line fuse (data for cutout type D)		pc x A	1 x 16
UVC lamp cable length (control-cabinet/reactor)		m	8
Power line cable length (control-cabinet/power plug)		m	no
Environmental temperature control-cabinet		°C	5 - 35
EVG ELECTRONIC BALLAST			3 AF400 T
Type			EVG 300 - 400 3,4 Ampere PH
Design		EVG	housing
Number of EVG´s		pcs	3
UVC lamps per EVG		pcs	1
System design			Bus-RS485
Control mode			digital
UVC power line regulation		%	50 - 120
Overall efficiency (normal operation EVG and UVC lamp)		%	≥ 90

TECHNICAL DATE SHEET

page 2/2

UVC multiple-lamp systems 400 W - **COMPACT T**

IRRADIATION CHAMBER			3 AF400 T
Irradiation chamber connection			DN 150
Connecting dimensions acc. Norm (flange made of compressed plate)			DIN 2642
Design - lay-out inlet to outlet flange			U - design
Irradiation chamber possible fitting positions	horizontal		yes
	vertical		yes
	reverse (UVC lamp)		yes
Material water-swept parts			stainless steel
Material number			1.4404
Material water-swept seals			O-rings EPDM
Dimensions	width	mm	364
	height (length)	mm	1.584
	depth	mm	285
	ED Ø	mm	256
Height IC including disassembling of the quartz tube			mm 3265
Quartz tubes flanged with adapter	ED Ø	mm	38
	length	mm	1.607
Number of quartz tubes			pcs 3
Weight without medium			approx. kg 64
Weight with medium			approx. kg 120
Irradiation chamber volume			approx. l 56
Drain / vent			1/2"
Irradiation chamber protection class			IP 65
Operating pressure (maximal)			bar 10
UVC LAMP			3 AF400 T
Type			AF400A
Product / Manufacturer			AQUAFIDES
Number of UVC lamps			pcs 3
UVC lamp kind			amalgam
UVC lamp power (Watt UVC per lamp - new lamp)			130,7
UVC lamp power (Watt UVC after 8.760 running hours per la W (UVC)			91,5
UVC lamp power @ 253,7 nm			% ≥ 85
UVC lamp wavelength @ ≤ 240 nm			filtrated
Power consumption per UVC lamp (including EVG)			W 395
UVC lamp currentconsumption per UVC lamp (normal opera			A 3,4
UVC lamp connection			special 4-pin
Lamp service life **			hours 12.000
UVC SENSORSYSTEM			3 AF400 T
Type			DigiNorm
Numbers of UVC sensors			pc 1
Design according ÖNORM M5873-1D			yes
Type tested according ÖNORM M5873-1D			yes
Recalibration according ÖNORM M5873-1D			yes
Calibration according ÖNORM M 5873-1D			yes
Recalibration time period			year 1
System design UVC sensor			Bus-RS485
Control mode			digital
UV measurement range			W/m ² 2 - 500
Output signal (switchable)			mA 0/4 - 20
Exactness of the measurements			% ± 2
Sensitive @ 254 nm			% ≥ 99
Temperature stability			°C 0 - 75
UVC sensor cabel length			m 9

* Medium temperature: in connection with the disinfection performance – please absolutely taking into account at dimensioning the plants

** Lamp quarantee and usage agreements are mentioned in the general Terms and Conditions of UVC lamps